

## QGIS Application - Feature request #13615

### Head/Tail Breaks

2015-10-15 06:12 PM - Spencer Gardner

|  |         |   |
|--|---------|---|
| <b>Status:</b>   | Open    | <b>Resolution:</b><br><b>Copied to github as #:</b> 21653 |
| <b>Priority:</b>   | Normal  |   |
| <b>Assignee:</b>   |         |   |
| <b>Category:</b>   | Unknown |   |
| <b>Pull Request or Patch supplied:</b>   |         |   |
| <b>Easy fix?:</b>  | No      |   |
| <b>Description</b>   |         |   |
| <p>Has there been any discussion about implementing head/tail breaks as a choropleth categorization on layers? It seems like it wouldn't be difficult to implement. Here's a paper that introduces the concept:</p> <p><a href="http://arxiv.org/pdf/1209.2801.pdf">http://arxiv.org/pdf/1209.2801.pdf</a></p> |         |   |

#### History

##### #1 - 2016-09-05 07:05 AM - Ding Martin

Hi

There is already a related implementation in Axwoman 6.3 (function name "HT mapping", <http://fromto.hig.se/~bjg/axwoman/>) about using head/tail breaks for choropleth maps, and for point and polyline feature as well.

Martin

##### #2 - 2017-05-01 12:47 AM - Giovanni Manghi

- *Easy fix? set to No*

##### #3 - 2017-09-22 10:07 AM - Jürgen Fischer

- *Category set to Unknown*