

QGIS Application - Bug report #13740

selectionChanged signal emitted on Mac without arguments

2015-11-02 10:57 AM - Jeff Caver

Status:	Closed	
Priority:	Normal	
Assignee:		
Category:	Python plugins	
Affected QGIS version:	2.12.0	Regression?: No
Operating System:	OSX	Easy fix?: No
Pull Request or Patch supplied:	No	Resolution:
Crashes QGIS or corrupts data:	No	Copied to github as #: 21767
Description		
<p>On OSX Yosemite, 10.10.5, both QGIS version 2.10 and 2.12 (KyngChaos installer), GDAL 1.11., When selectionChanged signal for QgsVectorLayer is connected to a user defined slot and the signal is emitted it doesn't send the selected, unselected, clearAndSelect arguments. Programmatically using select and setSelectedFeatures and manually selecting cause this behaviour. The problem does not exist for Windows 7 Professional or Ubuntu, only OSX.</p> <p>So:</p> <pre>lyr = iface.activeLayer() def mySlot(selected, unselected, clearAndSelect): print "here" lyr.selectionChanged.connect(mySlot)</pre> <p>Make a Selection on the canvas</p> <p>TypeError: mySlot() takes exactly 3 arguments (0 given)</p>		

Associated revisions

Revision 5f864229 - 2015-12-02 10:21 AM - Jürgen Fischer

- fix QgsFeatureIds typedef (fixes missing signal QgsVectorLayer.featuresDeleted and others; fixes #13740)
- add missing notes for PyNames
- include some missing new methods in bindings

(backported from commit b5794b2)

Revision b29cbbc6 - 2015-12-02 10:25 AM - Jürgen Fischer

sip bindings: fix QgsFeatureIds typedef (fixes missing signal QgsVectorLayer.featuresDeleted and others; fixes #13740)

(backported from commit b5794b2)

History

#1 - 2015-11-06 01:18 AM - Giovanni Manghi

- Priority changed from *Severe/Regression* to *Normal*
- Target version deleted (*Version 2.12*)

#2 - 2015-11-06 01:42 AM - Jürgen Fischer

- Subject changed from *selectionChanged signal emitted on Mac without arguments* to *selectionChanged signal emitted on Mac without arguments*

#3 - 2015-11-20 06:55 AM - Sebastian Dietrich

Note that selectionChanged is an overloaded signal that comes in two variants, one with 3 arguments and one without any arguments:

signals:

```
void selectionChanged( const QgsFeatureIds selected, const QgsFeatureIds deselected, const bool clearAndSelect );  
void selectionChanged();
```

Apparently the overload that is used by default on Windows is the first one, while on Mac the second one is used.

As a workaround try specifying the exact overload you want to connect:

```
lyr.selectionChanged['QgsFeatureIds', 'QgsFeatureIds', bool].connect(mySlot)
```

This also works on Windows.

#4 - 2015-11-20 11:12 AM - Nyal Dawson

Can you test with master? This should already be fixed

#5 - 2015-12-01 09:29 AM - Jeff Lifemapper Project

specifying the exact overload in mac doesn't work, for 2.12 or for 2.8.4 (returned to LTR on KyngChaos just to make sure)

```
lyr.selectionChanged['QgsFeatureIds', 'QgsFeatureIds', bool].connect(mySlot)
```

TypeError: C++ type 'QgsFeatureIds' is not supported as a signal argument type

#6 - 2015-12-01 11:46 AM - Nyal Dawson

- Status changed from *Open* to *Feedback*

Hi Jeff,

Can you test with a nightly snapshot please? We want to verify if changes made a few weeks ago fixed this, but they are NOT included in 2.12/2.8.4

#7 - 2015-12-01 11:55 AM - Jürgen Fischer

fixed in commit:b5794b2f

#8 - 2015-12-01 12:08 PM - Jeff Lifemapper Project

Yes, I found the nightly at <http://qgis.dakotacarto.com/>, and tested 2.13 dev. It seems to work, both as the default (sending the selected, deselected, clear and Select by default), and the 'QgsFeatureIds' doesn't throw an error should you have to specify the exact overload.

Thank you

#9 - 2015-12-02 01:22 AM - Jürgen Fischer

- *Status changed from Feedback to Closed*

Fixed in changeset commit:"5f86422942f73dc6e52c42945c4760fe0674d8c5".