# QGIS Application - Bug report #17611 r.in.lidar and other r.\* tools Error: 'Raster map not found' (worked until QGIS 2.18.14, GRASS 7.2.0)

2017-12-03 03:11 PM - Alen Mangafic

Status:	Open		
Priority:	High		
Assignee:			
Category:	Processing/GRASS		
Affected QGIS version:3.6.0		Regression?:	Yes
Operating System:		Easy fix?:	No
Pull Request or Patch supplied:		Resolution:	
Crashes QGIS or corru <b>pits</b> data:		Copied to github as #:	25508
Description			
The r.in.lidar in QGIS 2.18.14 and in GRASS 7.0.3 in Linux Mint and Windows 10 do the same error when running the tool:			
Algorithm r.in.lidar - Creates a raster map from LAS LiDAR points using univariate statistics. starting			
g.proj -c proj4="+proj=tmerc +lat_0=0 +lon_0=15 +k=0.9999 +x_0=500000 +y_0=-5000000 +ellps=GRS80			
+towgs84=0,0,0,0,0,0 +units=m +no_defs"			
g.region n=92000.0 s=91000.0 e=396000.0 w=395000.0 res=1			
r.in.lidar input="/home/alen/Desktop/TM_395_91.laz" method=mean type=FCELL zscale="1" percent="100" resolution="1" -e -o			
output=output412a4072b5e749b8b5eaa46a1e1a183foverwrite			
g.region raster=output412a4072b5e749b8b5eaa46a1e1a183f			
r.out.gdaloverwrite -c createopt="TFW=YES,COMPRESS=LZW" input=output412a4072b5e749b8b5eaa46a1e1a183f			
output="/home/alen/Desktop/obmocje.tif"			
Cleaning up temporary files			
Starting GRASS GIS			
Executing '/home/alen/.qgis2//processing/grass7_batch_job.sh'			
Default region was updated to the new projection, but if you have multiple mapsets `g.region -d` should be run in each to update			
the region from the default			
Projection information updated			
ERROR: Unable to open file			
ERROR: Raster map not found			
ERROR: Raster map or group not found			
Execution of '/home/alen/.qgis2//processing/grass7_batch_job.sh' finished.			
Cleaning up temporary files			
Cleaning up temporary files			
Starting GRASS GIS			
Executing '/home/alen/.qgis2//processing/grass7_batch_job.sh'			
ERROR: Raster map not found			
ERROR: Raster map or group not found			
Execution of '/home/alen/.qgis2//processing/grass7_batch_job.sh' finished.			
Cleaning up temporary files			
For Windows 10 I tried for both the OSGeo4W install and the direct install. I tried it also with QGIS 2.16.x and 2.14.x for both the OS			GIS 2.16.x and 2.14.x for both the OS. In
Linux Mint I apt-get autoremoved/autocleaned always after.			
In Windows 10, if I install GRASS 7.2.2 separately and run the tool from it, it works well. I tried to reconnect QGIS with the separate			to reconnect QGIS with the separate
GRASS install, but it does the same error again.			
It worked until a few updates ago; it works well in QGIS 2.18.5 with GRASS 7.2.0			

I noticed that also other r.\* GRASS tools don't work anymore.

## History

## #1 - 2017-12-04 10:23 PM - Alen Mangafic

- Assignee deleted (Alen Mangafic)

#### #2 - 2017-12-05 07:41 PM - Giovanni Manghi

- Category changed from GRASS to Processing/GRASS

- Assignee set to Giovanni Manghi

#3 - 2019-01-14 01:22 PM - Matthias Treitler

Same error with QGIS 3.4 under Linux

## #4 - 2019-01-17 12:58 PM - Giovanni Manghi

- Affected QGIS version changed from 2.18.14 to 3.4.3

- Subject changed from r.in.lidar and other r.\* tools Error: 'Raster map not found' in QGIS 2.18.14 GRASS 7.2.2 (worked until QGIS 2.18.14, GRASS

7.2.0) to r.in.lidar and other r.\* tools Error: 'Raster map not found' (worked until QGIS 2.18.14, GRASS 7.2.0)

- Assignee deleted (Giovanni Manghi)

## #5 - 2019-02-12 03:49 PM - Luigi Pirelli

- Assignee set to Luigi Pirelli

investigating

## #6 - 2019-02-12 04:57 PM - Luigi Pirelli

- Status changed from Open to Feedback

#### Hi

I'm not en expert using r.in.lidar, I had some problems putting it at work in grass directly, btw I was able to run it in grass74 and in qgis master via processing on linux.

Somethig failed during:

r.in.lidar input="/home/alen/Desktop/TM\_395\_91.laz" method=mean type=FCELL zscale="1" percent="100" resolution="1" -e -o output=output412a4072b5e749b8b5eaa46a1e1a183f --overwrite

I see that not setting filter Z and intensity range that are marked optionals, generate null data rasters.

Alen Mangafic can you check playing with r.in.lidar parameters in processing with latest qgis? In my case seems it's work with some parameter conditions.

#### #7 - 2019-02-12 05:15 PM - Luigi Pirelli

tested also on win10 and qgis-dev... seems its works correctly setting Z and intensity range. IMHO it can be closed

#### #8 - 2019-02-12 05:46 PM - Alen Mangafic

Luigi Pirelli wrote:

tested also on win10 and qgis-dev... seems its works correctly setting Z and intensity range. IMHO it can be closed

Hi, the default Z should be 1.0 (any scaling is highly optional) and the majority that users want is the import of Z values and not of the intensities. That could be the error sources. I will retry this days in Windows 10 and the last Ubuntu and let you know (I would do it right now if I wasn't chained in bed by flu).

Thank you very much for digging into it.

Regards,

Alen

#### #9 - 2019-02-12 06:10 PM - Luigi Pirelli

Z range is not related with Z scale (e.g. exageration). ZRange is used to cut a data cube within a specific Z range.

## #10 - 2019-02-12 06:14 PM - Alen Mangafic

Luigi Pirelli wrote:

Z range is not related with Z scale (e.g. exageration). ZRange is used to cut a data cube within a specific Z range.

Sorry, I undersood just now you takked about ranges. The minima and maxima of the dataset should be the default? I will check when on computer :)

## #11 - 2019-02-12 06:18 PM - Luigi Pirelli

no problem... thanks for checking. About setting by default min/max IMHO is the expected behaviour but no idea if before was able to setup the range automatically. IMHO if min=max => no range have to be set => gets all. But the issue is not related with if parameters are correct or not, but related if r.in.lidar works (in some way) or not.

## #12 - 2019-03-09 02:56 PM - Giovanni Manghi

- Affected QGIS version changed from 3.4.3 to 3.6.0
- Status changed from Feedback to Open
- Assignee deleted (Luigi Pirelli)
- Operating System deleted (Windows 10 and Linux Mint 18.3)

The module in native GRASS works:

#### a command like

r.in.lidar -e --overwrite input=/home/giovanni/Downloads/NEONDSSampleLiDARPointCloud.las output=test1 resolution=10

produces the expected output in native GRASS.

The problem in QGIS/Processing seems to be (possibly among the others) the parameters that SHOULD be optional (like the ranges) but are not, because are filled by default with values that is not possible to set to "none", and where we can't set by default anything other than "0".

In QGIS the base minimum commnad we produce is

r.in.lidar input="/home/giovanni/Downloads/NEONDSSampleLiDARPointCloud.las" method="mean" type="FCELL" zrange="0,0" zscale=1 intensity\_range="0,0" intensity\_scale=1 percent=100

that evidently is not 100% correct, at least for a general scenario.

## If we tweak the parameters to

r.in.lidar input="/home/giovanni/Downloads/NEONDSSampleLiDARPointCloud.las" method="mean" type="FCELL" zrange="-1000000,1000000" zscale=1 intensity\_range="-1000000,1000000" intensity\_scale=1 percent=100 resolution=10 -e

this **STILL** does not work in QGIS/Processing, but **DOES** work in the GRASS console, that indicated that there is even more than only problems with parameters defaults.