QGIS Application - Feature request #19278 Customize function "Update SQL Layer"

No

2018-06-27 10:47 AM - Michael Gieding

Status:	Open		
Priority:	Low		
Assignee:			
Category:	DB Manager		
Pull Request or Patch supplied:		Resolution:	

Copied to github as #: 27106

Easy fix?: Description

Hello everybody,

in QGIS 3.2, on Fedora 27, I used the function "Update SQL Layer" in the layer context menu for the first time.

When used, the DB-Manager opens with the query "select * from " and displays the result in the lower part of the window.

In my scenario I used the function on a layer that was loaded from a local postgresql database with an active filter to reduce the amount of data. The complete table has got originally 4 million rows with addresses.

Therefore "Update SQL Layer" initiated the "select * from ..." to load all 4 million rows and display them in the DB-Manager, right? My system completely hung up. In the end I had to kill QGIS and reboot the computer to continue my work.

OK, this could also happen, if I add a new layer from postgresql without filtering. But the above situation could also happen when I hit the function in the context menu by mistake.

I would like to suggest, that the function uses in addition to the "select..." the filter expression, if one is set for the layer.

Another option could be to add a limit to the select-statement.

Maybe it could be something for a future version.

Nevertheless many thanks to you all who work on QGIS.

Great job for a great peace of software.

Best regards,

Michael

2024-03-13 1/1