

QGIS Application - Bug report #20662

Processing modeler: PostgreSQL execute and load SQL saves password in cleartext

2018-11-28 05:24 PM - Samuel Oester

Status: Closed	
Priority: Normal	
Assignee:	
Category: Processing/Core	
Affected QGIS version: 3.4.2	Regression?: No
Operating System: MacOS 10.11.6	Easy fix?: No
Pull Request or Patch supplied: No	Resolution: no timely feedback
Crashes QGIS or corrupts data: No	Copied to github as #: 28482
Description	
If using a Postgres Layer with authentication stored in authentication DB as input in 'PostgreSQL execute and load SQL', credentials are stored in cleartext in output layer. Auth DB id is not used.	

History

#1 - 2019-01-24 11:40 AM - Victor Olaya

I dont understand the error. The algorithm that you mention does not take a layer as input. Instead, it takes a DB connection (just identified with its name), and then a SQL sentence.

I just checked that, for other algorithms that take vector layers, if the layer is based on a PostGIS connection, it adds the authid as param in the log, not the credentials

#2 - 2019-01-25 02:09 PM - Giovanni Manghi

- Status changed from Open to Feedback

#3 - 2019-03-08 11:02 AM - Giovanni Manghi

- Resolution set to no timely feedback

- Status changed from Feedback to Closed

Closing for lack of feedback.