

QGIS Application - Feature request #2293

Default styles for spatialite layers

2009-12-18 12:49 AM - mesajs -

Status:	Closed	
Priority:	Low	
Assignee:	nobody -	
Category:	Data Provider	
Pull Request or Patch supplied:		Resolution: fixed
Easy fix?:	No	Copied to github as #: 12353
Description		
It would be preferable to store default styles for spatialite layers in the database (e.g. in a qml table) instead of the project file. Styles to then automatically load when layers are added to a project. This approach works well with shapefiles, where the .qml file resides with the other files. Very handy when exporting layers to other users - they don't have to setup layer properties from scratch, and you don't have to provide the documentation to do so.		

Associated revisions

Revision 98fd25ec - 2009-12-23 10:17 PM - Jürgen Fischer

fix #2293

git-svn-id: <http://svn.osgeo.org/qgis/trunk/qgis@12604> c8812cc2-4d05-0410-92ff-de0c093fc19c

Revision 286893af - 2009-12-23 10:17 PM - Jürgen Fischer

fix #2293

git-svn-id: <http://svn.osgeo.org/qgis/trunk@12604> c8812cc2-4d05-0410-92ff-de0c093fc19c

History

#1 - 2009-12-23 01:18 PM - Jürgen Fischer

- Resolution set to fixed
- Status changed from Open to Closed

kind of duplicate of #1127. Although that didn't seem to work on spatialite layers. Fixed in commit:286893af (SVN r12605).

defaults styles for spatialite layers are also stored in the qmldb.