

Status:	Closed	
Priority:	Low	
Assignee:	Tim Sutton	
Category:	C++ Plugins	
Affected QGIS version:		Regression?: No
Operating System:	All	Easy fix?: No
Pull Request or Patch supplied:		Resolution: worksforme
Crashes QGIS or corrupts data:		Copied to github as #: 12584
Description		
<p>Imagine to have a vector and in its table of attributes you have a column called <code>"*colu"</code> and another called <code>"*coluna"</code>.</p> <p>Then set an action that will need to use the "coluna" field as variable.</p> <p>In the action command at some point you will then have <code>"%coluna"</code> as the variable part.</p> <p>But when you will run the action the variable part will be interpreted as <code>"%colu"</code> plus the letters <code>"na"</code></p> <p>I can't find any workaround to this.</p>		

History

#1 - 2010-03-07 11:25 AM - Jürgen Fischer

- Resolution set to worksforme
- Status changed from Open to Closed

#2 - 2010-03-07 11:28 AM - Jürgen Fischer

Replying to [comment:1 jef]:

```
<pre>
```

#3 - 2010-03-07 11:30 AM - Giovanni Manghi

Replying to [comment:1 jef]:

ok thanks. Is this documented?

#4 - 2010-03-08 12:29 AM - Otto Dassau

yes, it is documented in the user manual.

Replying to [comment:4 dassau]:



yes, it is documented in the user manual.



ok sorry, I missed it