

# QGIS Application - Bug report #2761

## .qpj files are saved in the wrong location

2010-05-29 04:08 AM - Giovanni Manghi

<b>Status:</b> Closed	
<b>Priority:</b> Low	
<b>Assignee:</b> nobody -	
<b>Category:</b> Vectors	
<b>Affected QGIS version:</b>	<b>Regression?:</b> No
<b>Operating System:</b> All	<b>Easy fix?:</b> No
<b>Pull Request or Patch supplied:</b>	<b>Resolution:</b> fixed
<b>Crashes QGIS or corrupts data:</b>	<b>Copied to github as #:</b> 12821
<b>Description</b>	
<p>Under linux are saved in the home directory, under windows in c:\ (under Seven are not saved at all because without admin privileges the user cannot write to c:\), regardless the location choosen to save a shapfile.</p> <p>Using qgis trunk.</p>	

### Associated revisions

---

#### Revision 497e3454 - 2010-05-29 01:39 PM - Jürgen Fischer

fix #2761

git-svn-id: <http://svn.osgeo.org/qgis/trunk/qgis@13589> c8812cc2-4d05-0410-92ff-de0c093fc19c

#### Revision 731c5b59 - 2010-05-29 01:39 PM - Jürgen Fischer

fix #2761

git-svn-id: <http://svn.osgeo.org/qgis/trunk@13589> c8812cc2-4d05-0410-92ff-de0c093fc19c

### History

---

#### #1 - 2010-05-29 04:39 AM - Jürgen Fischer

- Resolution set to fixed

- Status changed from Open to Closed

fixed in commit:731c5b59 (SVN r13590).