QGIS Application - Bug report #2894
Mapserver export: mangles shapefile paths in mapfile (layerid=0)

2010-07-19 08:10 AM - Sandro Santilli

Status:	Closed		
Priority:	Low		
Assignee:	Richard Duivenvoorde		
Category:	Python plugins		
Affected QGIS version:		**Regression?:**	No
Operating System:	All	**Easy fix?:**	No
Pull Request or Patch supplied:		**Resolution:**	fixed
Crashes QGIS or corrupts data:		**Copied to github as #:**	12954

Description

When exporting a project file to mapserver's mapfile the paths to shapefiles (DATA "/path/...") gets written with a "|layerid=0" substring appended, making them all unresolvable to mapserver.

The substring seems to be also in the project file itself, and works fine there (<datasource>) just needs to be split before writing to mapfile.

Associated revisions

Revision 014f5688 - 2010-07-19 05:28 PM - Jürgen Fischer

fix #2894

git-svn-id: http://svn.osgeo.org/qgis/trunk/qgis@13937 c8812cc2-4d05-0410-92ff-de0c093fc19c

Revision 75ce1bce - 2010-07-19 05:28 PM - Jürgen Fischer

fix #2894

git-svn-id: http://svn.osgeo.org/qgis/trunk@13937 c8812cc2-4d05-0410-92ff-de0c093fc19c

History

#1 - 2010-07-19 08:28 AM - Jürgen Fischer

- Resolution set to fixed

- Status changed from Open to Closed

fixed in commit:75ce1bce (SVN r13938).