

# QGIS Application - Bug report #7048

## QGIS Mapserver Internal Server Error

2013-01-25 09:31 AM - dr -

<b>Status:</b> Closed	
<b>Priority:</b> High	
<b>Assignee:</b> Marco Hugentobler	
<b>Category:</b> QGIS Server	
<b>Affected QGIS version:</b> master	<b>Regression?:</b> No
<b>Operating System:</b> Ubuntu	<b>Easy fix?:</b> No
<b>Pull Request or Patch supplied:</b> No	<b>Resolution:</b> worksforme
<b>Crashes QGIS or corrupts data:</b> No	<b>Copied to github as #:</b> 16136

### Description

Trying to run QGIS Mapserver on Ubuntu 12.04 (1.9.0+git20130123+595a45f~precise-ubuntugis1) installed from <http://qgis.org/ubuntugis-nightly>. Open web page [http://localhost/cgi-bin/qgis\\_mapserv.fcgi?SERVICE=WMS&#38;VERSION=1.3.0&#38;REQUEST=GetCapabilities](http://localhost/cgi-bin/qgis_mapserv.fcgi?SERVICE=WMS&#38;VERSION=1.3.0&#38;REQUEST=GetCapabilities) and get **Internal Server Error**. Apache logs:

```
[Sat Jan 26 00:29:55 2013] [warn] [client ::1] mod_fcgid: error reading data, FastCGI server closed connection
[Sat Jan 26 00:29:55 2013] [error] [client ::1] Premature end of script headers: qgis_mapserv.fcgi
[Sat Jan 26 00:29:55 2013] [error] [client ::1] File does not exist: /var/www/favicon.ico
[Sat Jan 26 00:30:00 2013] [error] mod_fcgid: process /usr/lib/cgi-bin/qgis_mapserv.fcgi(6333) exit(communication error), get signal 6, possible coredump generated
```

### History

#1 - 2013-01-25 09:49 AM - dr -

If put \*.qgs file into cgi-bin directory - all works fine. Is it normal behavior?

#2 - 2013-06-02 07:36 AM - Giovanni Manghi

- Resolution set to worksforme
- Status changed from Open to Closed

I guess you cannot ask for capabilities without specifying a project file (with &map=...). If a QGIS in in cgi-bin this is assumed as default.