

QGIS Application - Feature request #7436  
delete ESRI index files from shapefile after editing in QGIS

2013-03-25 04:34 AM - Gavin Fleming

<b>Status:</b>	Open	<b>Resolution:</b> <b>Copied to github as #:</b> 16397
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>	Unknown	
<b>Pull Request or Patch supplied:</b>		
<b>Easy fix?:</b>	No	
<b>Description</b>  1. shapefile comes with .sbn and .sbx index files from ESRI client 2. edit in QGIS, which does not maintain ESRI indexes. 3. Open shapefile again in ArcView (tested in 3.2 and 9.2) and shapefile appears corrupted, with many features missing. Even a 'bit in range' failure in AV 3.2. 4. delete .sbn and .sbx files and shapefile works perfectly  Solution: Whenever a shapefile is opened for editing (or when first commit is made) by QGIS, automatically delete ESRI index files if they exist.		
<b>Related issues:</b>		
Duplicates QGIS Application - Bug report # 5978: Missing features in shape-fi...		<b>Closed</b> <b>2012-07-09</b> <b>2012-07-09</b>

History

#1 - 2017-05-01 12:48 AM - Giovanni Manghi

- Easy fix? set to No

#2 - 2017-09-22 10:06 AM - Jürgen Fischer

- Category set to Unknown