

QGIS Application - Bug report #9514

Crash on loadNamedStyle against a layer created with an URI initialized with bogus aSql and aKeyColumn

2014-02-08 09:56 AM - Sandro Santilli

<b>Status:</b>	Closed	
<b>Priority:</b>	Normal	
<b>Assignee:</b>		
<b>Category:</b>		
<b>Affected QGIS version:</b>	master	<b>Regression?:</b> No
<b>Operating System:</b>		<b>Easy fix?:</b> No
<b>Pull Request or Patch supplied:</b>	No	<b>Resolution:</b>
<b>Crashes QGIS or corrupts data:</b>	Yes	<b>Copied to github as #:</b> 18105
<b>Description</b>		
<p>I made a mistake in calling QgsDataSourceURI.setDataSource from python and passing it 4 arguments instead of 5, practically I passed the "key column" as the 4th argument which was so interpreted as "aSql".</p> <p>Creating a QgsVectorLayer with the resulting URI resulted in corrupted memory and in a crash on the subsequent call to .loadNamedStyle.</p>		

Associated revisions

Revision 4c87b0c1 - 2014-02-08 07:14 PM - Jürgen Fischer

vector layer: don't crash on missing labels in invalid layers la(fix #9514)

History

#1 - 2014-02-08 10:16 AM - Jürgen Fischer

- Status changed from Open to Closed

Fixed in changeset commit:"4c87b0c123371b8a87a975746e8379643da97414".